



US006498476B1

(12) **United States Patent**
Raposa et al.

(10) **Patent No.:** **US 6,498,476 B1**
(45) **Date of Patent:** ***Dec. 24, 2002**

(54) **UNDERWATER HIGH SPEED PROJECTILE
SPEED SENSING DEVICE**

3,493,856 A * 2/1970 Wilson

324/180

(75) **Inventors:** John R. Raposa, Warren, RI (US);
Daniel P. Thivierge, Warren, RI (US)

* cited by examiner

(73) **Assignee:** The United States of America as
represented by the Secretary of the
Navy, Washington, DC (US)

Primary Examiner—Walter E. Snow*(74) Attorney, Agent, or Firm*—Michael J. McGowan;
James M. Kasischke; Michael F. Oglo

(*) **Notice:** Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) **Appl. No.:** 09/565,234

(22) **Filed:** Apr. 28, 2000

(51) **Int. Cl.⁷** G01P 3/66; G01P 3/80

(52) **U.S. Cl.** 324/178; 73/167

(58) **Field of Search** 324/178, 179,
324/180; 73/167

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,222,596 A * 12/1965 Mayer et al. 324/180

9 Claims, 2 Drawing Sheets

(57) ABSTRACT

A device for sensing projectile velocity in an underwater environment is provided. The device includes a plurality of evenly spaced break screen members positioned in a path of the projectile. Each break screen member includes a support member, a pair of transparent sheets spanning the support member, a continuous resistive trace sandwiched between the transparent sheets, and a sensing member correspondingly connected to each resistive trace. The sensing member includes means for outputting a signal responsive to impact of the projectile against the break screen, and a logic arrangement for determining a difference between impact of at two adjacent break screens throughout the run of break screens, thereby determining a velocity of the projectile.

